

T8 LED Light Tube/L05G-I33V Emergency LED tube



EMERGENCY POWER SUPPLY			
POWER Model	YJ2000-I33V-9W	YJ2000-I33V-18W	YJ2000-I33V-22W
Output power	9W	18W	22W
Illumination Intensity (LM)	1000	1800	2100
Emergency Intensity(LM)	500	600	700
Emergency Time(hrs)	4h	3.5h	3h

Model	Power	Dimension (mm)	LED Quantity (pcs)	Luminous (Frosted lens)	Luminous (Clear Lens)
L05G-I33V-600MM	9W	26*588(2FT)	110	1000±10%	1150lm±10%
L05G-I33V-1200MM	18W	26*1198(4FT)	210	1950lm±10%	2150lm±10%
L05G-I33V-1500MM	22W	26*1498(5FT)	240	2250lm±10%	2400lm±10%

Operation Temperature:	-20°C to 40°C
Working humidity:	96%
Voltage:	AC 100V-220V
Frequency:	50~60Hz
Power Factor:	>0.92
Power supply Efficiency:	0.86

B. Photometric Specifications

LED Luminous Efficiency:	> 100lm/w
CRL:	Ra: >70
CCT:	Warm White 3000k
	daylight white 4000k
	pure white 5500k
	cold white 6500k